



Copper Patch Panel Keystone Type



DATA SHEET

☎ +44 20 8895 6455
✉ info@webbinfra.com
🌐 www.webbinfra.com



1U CAT6/CAT6A/CAT7/CAT7A 24 Ports SFTP Keystone Jacks Patch Panel

This type of patch panel has SFTP shielded keystone jack patch panel with 1U 24 ports. With Color and numerical display of IDC modules at the panel rear.

Features

- SFTP shielded keystone jack patch panel with 1U 24 ports
- 19" mountable
- Designed for 22-26 AWG solid conductors



**Specifications are subject to change without notice based on technical recommendations and related product enhancements*



Specifications

- IDC - PC UL94V-0
- PCB - FR-4 1.60 mm (0.06") two impenetrable layers
- Housing: ABS 94V-0
- Metal housing: 1.50 mm dense metal
- Color pattern of conductors according to T568B & T568A
- Numerical display of ports on the front side of the panel with supplementary space for assigning numbers

Electrical Characteristics

- Basis UL 1863
- Current rating: 1.5 A maximum
- Voltage ranking: 150 V
- Operation temperature: -40 ~+ 70 degrees centigrade
- Contact resistance: 20 mohm
- Insulation: 500 mohm
- Dielectric voltage resistance: 1000 V AC RMS, 60Hz/1minute

Product Description

Part number	C.08.CPP.CA.24.SFTP.S.B.E
Certificate	CE, ISO & ROHS
Number of ports	24
Shield	SFTP
Windows label display	Yes

**Specifications are subject to change without notice based on technical recommendations and related product enhancements*