



FTTH Compact Closure HTSC-F01

Features

Compact design for FTTH application.

Hinged structure

Sheath retention & central strength member termination system included.

Ribbed closure construction-lightweight plastic offers strength and resistance to chemical and U.V attack

Installation and reentry with a minimum of tools

All hardware are captived

ROHS compliance

Application

Underground, Aerial , Duct, Wall Mounting

Specifications

Model No	Dimension(cm)	Ports	Capacity	Material
HTSC-F01	30 x 10.5 x 8	4 ports, each port for max diameter 10mm	12 splices	MPP



Fiber Optic Splice Closure HTSC-131 Features

- May be used for all fiber optic cable.
- Installation and reentry with a minimum of tools
- Easy to be opened or closed
- Re-enterable and reusable
- All hardware are included

Components

- Cover
- Bottom
- Seal gasket
- Clamp
- Splice Tray(with heat shrink sleeves)
- Cable fixing device
- Grounding wire
- Nylon tie
- Labeling paper
- Buffer tube
- Insulation tape

Optional Accessories

- Aerial mounting kits
- Duct mounting kits
- Pressure valve
- Grounding device

Application

Duct Mounting, Aerial Mounting, Underground, Wall Mounting

Specifications

Model No	Size(mm) LXWXH	Spliced fiber storage capacity	Cable ports	Max.diameter of cable(mm)	Splice Capacity of the tray
HTSC-131	420mm×127mm x72mm	Standard fiber 48 splices (2x24 splices)	4 ports	4 ports: each port for 1 cable with max 16 mm	Max.2 trays(24 cores), each tray up to 24 cores