

# Category 6 Modular Jack

Digilink Category 6 modular jack includes high performance Category 6 snap-in 8-position /8-contact (8P8C) jacks (Patent pending design) conforming to IEC 60603-7-2 (unshielded 100 MHz connectors). These jacks are designed for fast and easy snap-in and out of wall plates and patch panels. All jacks are designed in a 180° style and are available with back interconnection of 110 IDC blocks or special LSAPlus/110 IDC combination blocks in T568A, T568B.



### MECHANICAL SPECIFICATIONS

Plug Retention Force	14Kgf (140N)
Plug Reliability	750 cycle minimum
Jack Contact Material	Phosphor bronze 50µ" gold over 100µ" nickel plating
Conductor Compatibility	22-26AWG solid cable
Standard Colour	Blue, White, Yellow
Jack Mating Life	750 cycles

### ELECTRICAL SPECIFICATIONS

Voltage Rating	72 Vdc (max)
Propagation Delay	2.5ns Max @1-100 MHz
Contact Resistance	20 mΩ (max) per contact
Current Rating	1.5A max
Insulation Resistance	500MΩ(min)@500 Vdc

### PRODUCT FEATURES

- Robust and installer friendly design
- Compatible with 22-26 AWG solid cables
- Compatible to T568A, T568B wiring pattern
- Jacks with 180° from design-provide easier access
- UL-94V0 rated plastics
- ANSI/TIA-568-C.2 Category 6
- CENELEC EN 50173 & ISO/IEC-11801, Class E
- RoHS Compliant
- ETL Verified

NUMBER	DESCRIPTION
DC6KYSTU-WT	Category 6, UTP Keystone, Modular Jack, White Also available in Blue (BL), Yellow (YL), Green (GN), Red (RD), Black (BK)