

Category 6 UTP Patch Cords

Digilink Category 6 UTP patch cords are assemblies of 4 twisted pairs 23 AWG stranded wire cables with modular plugs (superior three piece connector) crimped on both ends. T568A and T568B wiring schemes are both available. The premium category moulded boot gives a designer look and snag less feature.



MECHANICAL SPECIFICATIONS

Length	1,2,3 & 5m
Standard Colour	Blue, Grey, Yellow
Wiring	23 AWG stranded unshielded
Plug Material	Gold over nickel contacts
RJ45 Plug	Polycarbonate plug

ELECTRICAL SPECIFICATIONS

Current Rating	1.5A max
Insulation Resistance	500MΩ/km(min)@500 Vdc
Voltage Rating	72 Vdc max
Contact Resistance	15 mΩ (max) per contact

PRODUCT FEATURES

- Available in the lengths of 1, 2, 3 & 5 m
- Cat 6 unshielded twisted pair 100Ω stranded cable
- Multi strand and highly flexible
- HDPE insulation over conductors, PVC jacket all over
- Individual cable pair separated by a PE former
- UL94V-0 rated plastic
- RoHS Compliant
- UL/ETL verified, UL listed
- ANSI/TIA-568-C.2 Category 6
- ISO/IEC-11801 Class E

NUMBER	DESCRIPTION
DC6PCURJ01GYM	Category 6, Patch Cord, UTP, 1M, Grey
DC6PCURJ02GYM	Category 6, Patch Cord, UTP, 2M, Grey
DC6PCURJ03GYM	Category 6, Patch Cord, UTP, 3M, Grey
DC6PCURJ05GYM	Category 6, Patch Cord, UTP, 5M, Grey
Also available in Blue (BLM), Yellow (YLM), Green (GRM), Red (RDM)	